

2026 GEO PRO

# G19SFD

Travel Trailer -- Printable spec sheet

<b>3,708 lb</b> UVW	<b>4,490 lb</b> GVWR*	<b>782 lb</b> CCC	<b>20 ft</b> LENGTH
------------------------	--------------------------	----------------------	------------------------

## DIMENSIONS

Exterior length	20' 0"
Exterior width	98"
Exterior height	10' 1"
Slide-outs	1

## CAPACITIES

Fresh water	31 gal
Grey water	27 gal
Black water	27 gal
Refrigerator	12V

## RUNNING GEAR

Axles	1 (single)
Hitch	Bumper Pull
Tires	Nitrogen-filled off-road w/ TPMS
Front cap	Fiberglass

## SLEEPING & LAYOUT

Sleeps	3
Primary bed	Front Murphy (queen)
Layout	Front Murphy bed / sofa, kitchen on slide, door-side dinette, full-length rear bath
Awning	14' (power)

## WEIGHTS

Unloaded vehicle weight	3,708 lbs*
GVWR (derived)	4,490 lbs*
Cargo carrying capacity	782 lbs
Hitch / tongue weight	490 lbs

## CONSTRUCTION

Frame	6-sided full-aluminum
Walls	Laminated Azdel composite
Roof	Vacuum-laminated fiberglass
Underbelly	Heated w/ radiant foil (N/A LE)

## GALLEY & BATH

Refrigerator	12V
Cooktop	3-burner + convection microwave
A/C	13,500 BTU
Furnace	20,000 BTU
Solar	Roof-solar prep + side port

**DATA COMPLETENESS** -- 94% — all dimensions, weights, capacities and tanks verified against the Forest River factory floorplan detail record; GVWR is derived as UVW plus CCC (Forest River does not print it) and is flagged, and the dealer-typical selling price is flagged

\* Flagged value: not separately published by the manufacturer, or carries a logged source note -- see the full entry online for detail.

Independent reference -- CamperTrailers.com is not affiliated with the manufacturer. Figures are base-unit as published; options change weights. Always confirm against the unit's certification / weight label and your tow vehicle's door-jamb placard before towing.

Full entry: [campertrailers.com/geopro-g19sfd.html](http://campertrailers.com/geopro-g19sfd.html)